

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Revision: 01.02.2023

Page 1/10

<ul> <li>1.1 Product ide</li> </ul>	ntifier	
• <b>1.2 Relevant ide</b> No further releva	entified use ant informati	I 700 Haftpromoter es of the substance or mixture and uses advised against ion available. nce / the mixture Priming
<ul> <li>1.3 Details of th</li> <li>Manufacturer/S</li> <li>FEYCOLOR Gm</li> <li>Maxhüttenstraße</li> <li>93055 Regensbu</li> <li>Germany</li> </ul>	b <b>upplier:</b> hbH e 6	of the safety data sheet
Tel.: +49 (0) 941 Fax: +49 (0) 941 info@feycolor.cc	-60497-30	ycolor.com
Office hours: Monday - Thursc Friday: 08:00 - 1		12:00 und 13:00 - 16:00
Email: sd@feyco www.feycolor.co · <b>1.4 Emergency</b>	m	number: +49 (0) 700 24 11 21 12 (FCM)
SECTION 2: H	azards ide	entification
· 2.1 Classificatio	on of the su	entification ubstance or mixture o Regulation (EC) No 1272/2008
• 2.1 Classification a	on of the su	ubstance or mixture o Regulation (EC) No 1272/2008
• 2.1 Classification • Classification a	n of the su ccording to H225	ubstance or mixture o Regulation (EC) No 1272/2008
• 2.1 Classification a • Classification a flame Flam. Liq. 2	n of the su ccording to H225	ubstance or mixture o Regulation (EC) No 1272/2008
<ul> <li>2.1 Classification a</li> <li>Classification a</li> <li>flame</li> <li>Flam. Liq. 2</li> <li>health</li> <li>STOT RE 2</li> </ul>	hazard H373 H304 H315 H319	ubstance or mixture o Regulation (EC) No 1272/2008 Highly flammable liquid and vapour. May cause damage to organs through prolonged or repeated exposure.
<ul> <li>2.1 Classification a</li> <li>Classification a</li> <li>flame</li> <li>Flam. Liq. 2</li> <li>health</li> <li>STOT RE 2</li> <li>Asp. Tox. 1</li> <li>Skin Irrit. 2</li> <li>Eye Irrit. 2</li> </ul>	hazard H373 H304 H315 H319 H335-H3	ubstance or mixture o Regulation (EC) No 1272/2008 Highly flammable liquid and vapour. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation.
<ul> <li>2.1 Classification a</li> <li>Classification a</li> <li>Classification a</li> <li>flame</li> <li>Flam. Liq. 2</li> <li>flame</li> <li>Flam. Liq. 2</li> <li>health</li> <li>STOT RE 2</li> <li>Asp. Tox. 1</li> <li>Skin Irrit. 2</li> <li>Eye Irrit. 2</li> <li>STOT SE 3</li> <li>Aquatic Chronic</li> <li>2.2 Label elemet</li> </ul>	n of the subcording to H225 hazard H373 H304 H315 H319 H335-H3 3 H412 ents	Ubstance or mixture o Regulation (EC) No 1272/2008 Highly flammable liquid and vapour. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. 336 May cause respiratory irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.
<ul> <li>2.1 Classification a</li> <li>Classification a</li> <li>Classification a</li> <li>flame</li> <li>Flam. Liq. 2</li> <li>flame</li> <li>Flam. Liq. 2</li> <li>health</li> <li>STOT RE 2</li> <li>Asp. Tox. 1</li> <li>Skin Irrit. 2</li> <li>Eye Irrit. 2</li> <li>STOT SE 3</li> <li>Aquatic Chronic</li> <li>2.2 Label eleme</li> <li>Labelling accor</li> </ul>	H225 H225 Hazard H373 H304 H315 H319 H335-H3 3 H412 ents rding to Re	Jubstance or mixture         o Regulation (EC) No 1272/2008         Highly flammable liquid and vapour.         May cause damage to organs through prolonged or repeated exposure.         May be fatal if swallowed and enters airways.         Causes skin irritation.         Causes serious eye irritation.         B36 May cause respiratory irritation. May cause drowsiness or dizziness.



Page 2/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

### Trade name: FEYCARBON 700 Haftpromoter

Hazard picto	(Contd. of page
	yrains
<b>&lt; ()) &gt; (</b> )	
GHS02 GH	S07 GHS08
Signal word	Danger
Hazard-deter	mining components of labelling:
Xylene	
Ethyl acetate	
Solvent napht	ha (petroleum), light arom.
Ethylbenzene	
Hazard state	nents
	ighly flammable liquid and vapour.
	auses skin irritation.
	auses serious eye irritation.
	ay cause respiratory irritation. May cause drowsiness or dizziness.
	ay cause damage to organs through prolonged or repeated exposure.
	ay be fatal if swallowed and enters airways.
	armful to aquatic life with long lasting effects.
Precautionar	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P321 P331	Specific treatment (see on this label). Do NOT induce vomiting.
	P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water
F 3037F 301+F	shower].
P305+P351+F	2338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,
	present and easy to do. Continue rinsing.
P362+P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container in accordance with local/regional/national/internation
	regulations.
2.3 Other haz	
	3T and vPvB assessment
PBT: Not app	licable.

appi vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3) GB



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCARBON 700 Haftpromoter

	(Co	ntd. of page
Dangerous components:		
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46	Ethyl acetate Flam. Liq. 2, H225;	25-50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	25-50%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. 🚸 Flam. Liq. 3, H226; 🚸 Asp. Tox. 1, H304	2.5-<10%
CAS: 123-42-2 EINECS: 204-626-7 Reg.nr.: 01-2119473975-21	4-hydroxy-4-methylpentan-2-one	2.5-<10%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	2.5-<10%
CAS: 95-63-6 EINECS: 202-436-9	1,2,4-trimethylbenzene Flam. Liq. 3, H226; Aquatic Chronic 2, H411; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<10%

### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Seek immediate medical advice.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

(Contd. on page 4)

GB



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCARBON 700 Haftpromoter

### **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away. · 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. · 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. · 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. **SECTION 7: Handling and storage** 

### · 7.1 Precautions for safe handling

Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

8.1 Control parameters

· Ingredients with limit values that re	quire monitoring at the workplace:

### 141-78-6 Ethyl acetate

WEL Short-term value: 1468 mg/m<sup>3</sup>, 400 ppm Long-term value: 734 mg/m<sup>3</sup>, 200 ppm

### 1330-20-7 Xylene

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm Long-term value: 220 mg/m<sup>3</sup>, 50 ppm Sk; BMGV

(Contd. on page 5)

(Contd. of page 3)



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCARBON 700 Haftpromoter

(Contd. of page 4
123-42-2 4-hydroxy-4-methylpentan-2-one
WEL Short-term value: 362 mg/m <sup>3</sup> , 75 ppm
Long-term value: 241 mg/m³, 50 ppm
100-41-4 Ethylbenzene
WEL Short-term value: 552 mg/m³, 125 ppm
Long-term value: 441 mg/m <sup>3</sup> , 100 ppm
Sk
95-63-6 1,2,4-trimethylbenzene
WEL Long-term value: 125 mg/m³, 25 ppm
ILV
· Ingredients with biological limit values:
1330-20-7 Xylene
BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid
• Additional information: The lists valid during the making were used as basis

Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

• Appropriate engineering controls No further data; see item 7.

· Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes. Avoid contact with the eyes and skin.

### • Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

### · Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



Safety data sheet according to 1907/2006/EC, Article 31


Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

(Contd. of page 5)

### Trade name: FEYCARBON 700 Haftpromoter



Tightly sealed goggles

9.1 Information on basic physical and chemical	properties
General Information Physical state	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	
range	77-78 °C (141-78-6 Ethyl acetate)
Flammability	Highly flammable.
Lower and upper explosion limit	
	1.1  (a)  % (1220.20.7  Vylana)
Lower:	1.1 Vol % (1330-20-7 Xylene)
Upper:	11.5 Vol % (141-78-6 Ethyl acetate)
Flash point:	10 °C (DIN EN ISO 1523:2002)
Ignition temperature:	430 °C (DIN 51794, 100-41-4 Ethylbenzene) Not determined.
Decomposition temperature:	
pH Viacesitur	Not determined.
Viscosity:	12 - (DIN 52211/4)
Kinematic viscosity at 20 °C	13 s (DIN 53211/4) Not determined.
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	
Vapour pressure at 20 °C:	97 hPa (141-78-6 Ethyl acetate)
Density and/or relative density	
Density at 20 °C:	0.911 g/cm <sup>3</sup> (DIN EN ISO 2811-1)
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health	and
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosivair/vapour mixtures are possible.
Solvent content:	
VOC (EC)	95.53 %
Solids content (weight-%):	4.4 %

Page 6/10



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCARBON 700 Haftpromoter

		(Contd. of page
Change in condition		
Evaporation rate	Not determined.	
Information with regard to physical hazard class	SSes	
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Highly flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flammat	ble	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

### **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: Carbon monoxide

### **SECTION 11: Toxicological information**

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

### · LD/LC50 values relevant for classification:

1330-20-7 Xylene			
Oral	LD50	5,251 mg/kg (rat)	
	LD50	5,251 mg/kg (rat) >5,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	29 mg/l (rat)	

Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye irritation.

• STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

· STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

• Aspiration hazard May be fatal if swallowed and enters airways.

(Contd. on page 8)

GB



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

(Contd. of page 7)

### Trade name: FEYCARBON 700 Haftpromoter

#### · 11.2 Information on other hazards

### Endocrine disrupting properties

None of the ingredients is listed.

### **SECTION 12: Ecological information**

#### · 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN number or ID number		
· ADR, IMDG, IATA	UN1263	
14.2 UN proper shipping name		
ADR	UN1263 PAINT	
· IMDG, IATA	PAINT	

Page 8/10



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCARBON 700 Haftpromoter

	(Contd. of page
<ul> <li>14.3 Transport hazard class(es)</li> </ul>	
ADR	
· Class	3 (F1) Flammable liquids.
Label	3
· IMDG, IATA	
3	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
EMS Number:	F-E, <u>S-E</u>
Stowage Category	В
<ul> <li>14.7 Maritime transport in bulk according to IM instruments</li> </ul>	IO Not applicable.
	Not applicable.
· Transport/Additional information:	
· ADR	51
<ul> <li>Limited quantities (LQ)</li> <li>Transport category</li> </ul>	5L 2
• Tunnel restriction code	D/E
·IMDG	
· Limited quantities (LQ)	5L
UN "Model Regulation":	UN 1263 PAINT, 3, II

### **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- $\cdot$  Qualifying quantity (tonnes) for the application of lower-tier requirements  $5{,}000\ t$
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 10)

<sup>–</sup> GB



Printing date 01.02.2023

Page 10/10

## Safety data sheet

according to 1907/2006/EC, Article 31 Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCARBON 700 Haftpromoter

· National regulations:

(Contd. of page 9)

· Additional classification according to Decree on Hazardous Materials, Annex II:

Class | Share in %

NK 50-100

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information** 

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

### Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 \* Data compared to the previous version altered.