

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Revision: 01.02.2023

Page 1/11

· 1.1 Product identifier · Trade name: FEYCOFIX 336 HS Einschichtlack 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Paint 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: **FEYCOLOR GmbH** Maxhüttenstraße 6 93055 Regensburg Germany Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30 info@feycolor.com www.feycolor.com Office hours: Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00 Friday: 08:00 - 12:00 Email: sd@feycolor.com www.feycolor.com · 1.4 Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM) **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 flame Flam. Liq. 3 H226 Flammable liquid and vapour. environment Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. · 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. (Contd. on page 2)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCOFIX 336 HS Einschichtlack

· Hazard pictogr	(Contd. of page 1)
nazaru pictogi	
GHS02 GHS0	07 GHS09
· Signal word W	arning
Hazard statem	•
	le liquid and vapour.
H315 Causes s	
	erious eye irritation.
	quatic life with long lasting effects.
Precautionary	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P3	53 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or
	shower].
P305+P351+P3	38 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P403+P235	Store in a well-ventilated place. Keep cool.
Additional info	
	ns cobalt bis(2-ethylhexanoate). May produce an allergic reaction.
2.3 Other haza	
	and vPvB assessment
PBT: Not applic	
vPvB: Not appli	icable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

~ ~	aoro		~~~~	
	norn	IIC.		

CAS: 1330-20-7	Xylene	5-<10%
EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	 Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 	
	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226;	2.5-<10%
	Hydrocarbons, C9, aromatics ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335-H336, EUH066	2.5-<5%



Page 3/11

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCOFIX 336 HS Einschichtlack

		(Contd. of page 2)
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40	Trizinc bis(orthophosphate) 〈 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.25-<2.5%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	<2.5%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066	<2.5%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate 🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336, EUH066	1-<2.5%
CAS: 78-83-1 EINECS: 201-148-0 Reg.nr.: 01-2119484609-23	Isobutanol	≥1-<2.5%
CAS: 2457-01-4 EINECS: 219-535-8	barium bis(2-ethylhexanoate) ♦ Repr. 2, H361d; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; Acute Tox. 4, H332	<1%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119524678-29	cobalt bis(2-ethylhexanoate) Repr. 1B, H360Fd; Aquatic Acute 1, H400; Eye Irrit. 2, H319; Skin Sens. 1A, H317; Aquatic Chronic 3, H412 r the wording of the listed bezerd phrases refer to section 16	<0.1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

(Contd. of page 3)

Trade name: FEYCOFIX 336 HS Einschichtlack

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

- Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No special measures required. No special precautions are necessary if used correctly.

- · Information about fire and explosion protection:
- Keep ignition sources away Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.

• Storage class: 3

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

 Ingredients with limit values that require monitoring at the workplace:

 1330-20-7 Xylene

 WEL
 Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

 108-65-6 2-Methoxy-1-methylethyl acetate

 WEL
 Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

 100-41-4 Ethylbenzene

 WEL
 Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk

(Contd. on page 5)

Page 4/11



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCOFIX 336 HS Einschichtlack

	(Contd. of pa
	36-4 n-Butyl acetate
WEL	Short-term value: 966 mg/m ³ , 200 ppm
	Long-term value: 724 mg/m³, 150 ppm
78-83	3-1 Isobutanol
WEL	Short-term value: 231 mg/m ³ , 75 ppm
	Long-term value: 154 mg/m³, 50 ppm
	52-7 cobalt bis(2-ethylhexanoate)
WEL	Long-term value: 0.1 mg/m ³
	as Co; Carc, Sen
· Ingre	edients with biological limit values:
1330	-20-7 Xylene
BMG	V 650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid tional information: The lists valid during the making were used as basis.
· Indiv · Gene Keep Imme Wash Avoid Avoid • Resp · Hand	 Propriate engineering controls No further data; see item 7. Pridual protection measures, such as personal protective equipment Pridual protective and hygienic measures: Protective and solve and contaminated clothing Print hands before breaks and at the end of work. Protection: Use suitable respiratory protective device only when aerosol or mist is formed. Protection Protection
	Protective gloves (EN 374) glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
·Mato	rial of gloves

and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

GB

Page 5/11



Page 6/11

Safety data sheet according to 1907/2006/EC, Article 31


Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

(Contd. of page 5)

Trade name: FEYCOFIX 336 HS Einschichtlack



Tightly sealed goggles

SECTION 9: Physical and chemical properties	S
• 9.1 Information on basic physical and chemical pr	operties
· General Information	•
· Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling	
range	137-143 °C (1330-20-7 Xylene)
· Flammability	Flammable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	24 °C (DIN EN ISO 1523:2002, 1330-20-7 Xylene)
Ignition temperature:	315 °C (DIN 51794, 108-65-6 2-Methoxy-1-methylethy
.g	acetate)
Decomposition temperature:	Not determined.
• pH	Not determined.
· Viscosity:	Not determined.
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	5,000 mPas
· Solubility	5,000 m as
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	6.7-8.2 hPa (1330-20-7 Xylene)
Density and/or relative density	
Density at 20 °C:	1.597 g/cm³ (DIN EN ISO 2811-1)
· Relative density	Not determined.
· Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health and	a
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive
Onlying the sector of	air/vapour mixtures are possible.
Solvent content:	04.40.04
· VOC (EC)	24.18 %
· Solids content (weight-%):	75.8 %
	(Contd. on page



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCOFIX 336 HS Einschichtlack

Change in condition Evaporation rate	Not determined.	
Information with regard to physical hazard cl	asses	
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamma	able	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- Acute toxicity Based on available data, the classification criteria are not met.
- Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye irritation.

· 11.2 Information on other hazards

Endocrine disrupting properties

78-93-3 Methyl ethyl ketone

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

• 12.2 Persistence and degradability No further relevant information available.

(Contd. on page 8)

List II

- GB

(Contd. of page 6)

Page 7/11



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

(Contd. of page 7)

Trade name: FEYCOFIX 336 HS Einschichtlack

· 12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

• **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.

- 12.7 Other adverse effects
- · Remark: Toxic for fish

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name	
ADR	UN1263 PAINT, ENVIRONMENTALLY HAZARDOUS
·IMDG	PAINT (Solvent naphtha, Trizinc bis(orthophosphate) MARINE POLLUTANT
· IATA	PAINT
· 14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
· Label	3



Page 9/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCOFIX 336 HS Einschichtlack

	(Contd. of page	
·IMDG		
Class Label	3 Flammable liquids. 3	
·IATA		
Class	3 Flammable liquids.	
· Label	3	
· 14.4 Packing group · ADR, IMDG, IATA	III	
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances	
· Marine pollutant:	Trizinc bis(orthophosphate) Symbol (fish and tree)	
· Special marking (ADR):	Symbol (fish and tree)	
14.6 Special precautions for user	Warning: Flammable liquids.	
 Hazard identification number (Kemler code): EMS Number: 	30 F-E,S-E	
· Stowage Category	A	
• 14.7 Maritime transport in bulk according to IN	10	
instruments	Not applicable.	
· Transport/Additional information:		
· ADR		
Limited quantities (LQ)	5L	
 Transport category Tunnel restriction code 	3 D/E	
· Remarks:	≤ 5 I: 2.2.3.1.5 ADR	
·IMDG		
· Limited quantities (LQ)	5L	
Remarks:	\leq 5 l: 2.2.3.1.5 IMDG	
· UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALL HAZARDOUS	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCOFIX 336 HS Einschichtlack

(Contd. of page 9)

Page 10/11

- Seveso category
 E2 Hazardous to the Aquatic Environment
 P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	10-25

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H360Fd May damage fertility. Suspected of damaging the unborn child.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids Category 2
- Flam. Liq. 3: Flammable liquids Category 3
- Acute Tox. 4: Acute toxicity Category 4

GB



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCOFIX 336 HS Einschichtlack

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1A: Skin sensitisation – Category 1A Repr. 1B: Reproductive toxicity – Category 1B Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 * * Data compared to the previous version altered. (Contd. of page 10)

GB

Page 11/11