



according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 4 (replaces version 3) Revision: 01.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: FEYCOPLAST 771 DS SFC
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Priming
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

FEYCOLOR GmbH Maxhüttenstraße 6 93055 Regensburg Germany

Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30

info@feycolor.com www.feycolor.com

Office hours:

Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00

Friday: 08:00 - 12:00

Email: sd@feycolor.com www.feycolor.com

• 1.4 Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



STOT SE 3

H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 4 (replaces version 3) Revision: 01.02.2023

Trade name: FEYCOPLAST 771 DS SFC

(Contd. of page 1)

· Hazard pictograms







GHS02 GHS07 GHS09

· Signal word Warning

· Hazard-determining components of labelling:

2-Methoxy-1-methylethyl acetate

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or

showerj

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

· Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	10-25%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336, EUH066	2.5-<10%
CAS: 111-76-2 EINECS: 203-905-0 Reg.nr.: 01-2119475108-36	2-Butoxyethanol Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg	2.5-<10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-<2.5%
		(Contd. on page 3



Page 3/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 4 (replaces version 3) Revision: 01.02.2023

Trade name: FEYCOPLAST 771 DS SFC

CAS: 1314-13-2 | zinc oxide | ≥0.25-<2.5% | EINECS: 215-222-5 | Reg.nr.: 01-2119463881-32 | Zinc oxide | 20.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2.5% | ≥0.25-<2

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 4 (replaces version 3) Revision: 01.02.2023

Trade name: FEYCOPLAST 771 DS SFC

(Contd. of page 3)

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingradiant	s with	limit	values	that	require	monitoring	at the	workplace:
III WI EWIEII	.S WILII	1111111	values	ulat	IEUUIIE	IIIOIIILOIIII	at tile	WUINDIACE.

108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

Sk

111-76-2 2-Butoxyethanol

WEL Short-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm Sk, BMGV

1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

· Ingredients with biological limit values:

111-76-2 2-Butoxyethanol

BMGV 240 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: butoxyacetic acid

1330-20-7 Xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

(Contd. on page 5)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 4 (replaces version 3) Revision: 01.02.2023

Trade name: FEYCOPLAST 771 DS SFC

(Contd. of page 4)

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined.

• Melting point/freezing point:

Undetermined.

· Boiling point or initial boiling point and boiling

range 124 °C Flammability Flammable.

· Lower and upper explosion limit · Lower: 1.5 Vol %

• **Upper:** 10.8 Vol % • **Flash point:** 24 °C (DIN EN ISO 1523:2002)

• Ignition temperature: 240 °C (DIN 51794)
• Decomposition temperature: Not determined.

Not determined.

· Viscosity:
· Kinematic viscosity at 20 °C 100 s (DIN 53211/4)

• Kinematic viscosity at 20 °C 100 s (DIN 53211/4) • Dynamic: Not determined.

(Contd. on page 6)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 4 (replaces version 3) Revision: 01.02.2023

3.4 hPa

Trade name: FEYCOPLAST 771 DS SFC

(Contd. of page 5)

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C:

· Density and/or relative density

Density at 00 00.

Density at 20 °C: 1.353 g/cm³ (DIN EN ISO 2811-1)

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and

environment, and on safety.

· **Auto-ignition temperature:** Product is not selfigniting.

• **Explosive properties:** Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Solvent content:

· VOC (EC) 36.28 % · Solids content (weight-%): 63.3 %

· Change in condition

Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

• Flammable liquids Flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures, which emit flammable gases in contact with water
 Oxidising liquids
 Oxidising solids
 Oxidising solids

Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives


Void

Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 7)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 4 (replaces version 3) Revision: 01.02.2023

Trade name: FEYCOPLAST 771 DS SFC

· 10.6 Hazardous decomposition products: Carbon monoxide

(Contd. of page 6)

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

78-93-3 Methyl ethyl ketone

List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA UN1263
- 14.2 UN proper shipping name
- · ADR UN1263 PAINT, ENVIRONMENTALLY HAZARDOUS

(Contd. on page 8)





Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 4 (replaces version 3) Revision: 01.02.2023

Trade name: FEYCOPLAST 771 DS SFC

	(Contd. of page
· IMDG · IATA	PAINT (zinc oxide, Solvent naphtha), MARIN POLLUTANT PAINT
14.3 Transport hazard class(es)	LAINT
ADR	
1	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG	
· Class	3 Flammable liquids.
·Label	3
· Class · Label	3 Flammable liquids.3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Product contains environmentally hazardous substance Solvent naphtha
· Marine pollutant:	Yes
· Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, <u>S-E</u>
Stowage Category	A
 14.7 Maritime transport in bulk according to IM instruments 	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
Transport category	3
· Tunnel restriction code · Remarks:	D/E ≤ 5 l: 2.2.3.1.5 ADR

(Contd. on page 9)





according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Version number 4 (replaces version 3) Revision: 01.02.2023

Trade name: FEYCOPLAST 771 DS SFC

(Contd. of page 8)

· IMDG · Limited quantities (LQ) · Remarks:	5L ≤ 5 l: 2.2.3.1.5 IMDG
· UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 10)



Page 10/10

Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 01.02.2023 Printing date 01.02.2023 Version number 4 (replaces version 3)

Trade name: FEYCOPLAST 771 DS SFC

(Contd. of page 9)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* Data compared to the previous version altered.