

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023 Vers

Version number 2 (replaces version 1)

Revision: 01.02.2023

Page 1/9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

- · Trade name: FEYCOPOX 518 2K HS EG Primer
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Priming
- · 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: FEYCOLOR GmbH Maxhüttenstraße 6 93055 Regensburg Germany

Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30 info@feycolor.com www.feycolor.com

Office hours: Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00 Friday: 08:00 - 12:00

Email: sd@feycolor.com www.feycolor.com

· 1.4 Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Irrit. 2 H315 Causes skin irritation.Eye Irrit. 2 H319 Causes serious eye irritation.Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



· Signal word Warning

(Contd. on page 2)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 2 (replaces version 1)

Revision: 01.02.2023

Page 2/9

Trade name: FEYCOPOX 518 2K HS EG Primer

 smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 2.3 Other hazards 		(Contd. of page 1
Bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight 700-1100) oxirane, mono[(C12-14-alkyloxy)methyl] derivs Phenol, methylstyrenated Hazard statements H226 Flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 2.3 Other hazards Superventile and	Hazard-deterr	nining components of labelling:
oxirane, mono[(C12-14-alkyloxy)methyl] derivs Phenol, methylstyrenated Hazard statements H226 Flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H319 Quases an allergic skin reaction. Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 2.3 Other hazards		
 Phenol, methylstyrenated Hazard statements H226 Flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P358 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, ir present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 		
Hazard statements H226 Flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [o shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 2.3 Other hazards Eulergic reaction.		
 H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [o shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 2.3 Other hazards 		
 H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [o shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 2.3 Other hazards 	H226 Flamma	ble liquid and vapour.
 H317 May cause an allergic skin reaction. Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [o shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 2.3 Other hazards 		
Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [o shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 2.3 Other hazards Description	H319 Causes	serious eye irritation.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [o shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 2.3 Other hazards 	H317 May cau	se an allergic skin reaction.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [o shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 2.3 Other hazards 	Precautionary	/ statements
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [o shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 	P210	
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [o shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 2.3 Other hazards 		smoking.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [o shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 2.3 Other hazards 	P261	
shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 2.3 Other hazards	P280	
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 2.3 Other hazards 	P303+P361+P	353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [o
present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 2.3 Other hazards		•
P403+P235 Store in a well-ventilated place. Keep cool. Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 2.3 Other hazards	P305+P351+P	
Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 2.3 Other hazards		
EUH205 Contains epoxy constituents. May produce an allergic reaction. 2.3 Other hazards		· · ·
2.3 Other hazards		
Results of PBT and vPvB assessment		
PBT: Not applicable.	PBT: Not appl	icable.

• vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Г

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 25068-38-6	Bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight 700-1100) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205	10-25%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35	1-methoxy-2-propanol ♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	2.5-<10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
CAS: 68609-97-2 EINECS: 271-846-8 Reg.nr.: 01-2119485289-22	oxirane, mono[(C12-14-alkyloxy)methyl] derivs Skin Irrit. 2, H315; Skin Sens. 1, H317	2.5-<10%
CAS: 68512-30-1 EINECS: 270-966-8 Reg.nr.: 01-2119555274-38	Phenol, methylstyrenated ♦ Skin Irrit. 2, H315; Skin Sens. 1B, H317; Aquatic Chronic 3, H412	≥1-<2.5%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	<2.5%



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 2 (replaces version 1)

Revision: 01.02.2023

(Contd. of page 2)

Trade name: FEYCOPOX 518 2K HS EG Primer

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately rinse with water.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

- Ensure adequate ventilation. 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

GB



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 2 (replaces version 1)

Revision: 01.02.2023

(Contd. of page 3)

Trade name: FEYCOPOX 518 2K HS EG Primer

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Store away from foodstuffs.

- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk

1330-20-7 Xylene WEL Short-term value: 441 mg/m³, 100 ppm

Long-term value: 220 mg/m³, 50 ppm Sk: BMGV

100-41-4 Ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk

Ingredients with biological limit values:

1330-20-7 Xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

GB



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 2 (replaces version 1)

Revision: 01.02.2023

Trade name: FEYCOPOX 518 2K HS EG Primer

Hand protection

(Contd. of page 4)

Page 5/9

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

9.1 Information on basic physical and chemical p	roperties
General Information	
Physical state	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	
range	120.3 °C (107-98-2 1-methoxy-2-propanol)
Flammability	Flammable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	24 °C (DIN EN ISO 1523:2002, 1330-20-7 Xylene)
Ignition temperature:	270 °C (DIN 51794, 107-98-2 1-methoxy-2-propanol)
Decomposition temperature:	Not determined.
рН	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic at 20 °C:	8,000-10,000 mPas
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	12 hPa (107-98-2 1-methoxy-2-propanol)
Density and/or relative density	
Density at 20 °C:	1.782 g/cm³ (DIN EN ISO 2811-1)

GB



Page 6/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 2 (replaces version 1)

Revision: 01.02.2023

Trade name: FEYCOPOX 518 2K HS EG Primer

Deletive density	(Contd. of page
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of healt	th and
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosiv
	air/vapour mixtures are possible.
Solvent content:	
VOC (EC)	20.29 %
Solids content (weight-%):	79.7 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard cl	asses
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flamma	able
gases in contact with water	Void
	Void
Oxidising liquids	VOIG
Oxidising liquids Oxidising solids	Void
Oxidising solids	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Possible in traces. Nitrogen oxides

Hydrogen chloride (HCI) Carbon monoxide

GB



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 2 (replaces version 1)

Revision: 01.02.2023

(Contd. of page 6)

List II

Trade name: FEYCOPOX 518 2K HS EG Primer

Nitrogen oxides (NOx)

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- 11.2 Information on other hazards
- Endocrine disrupting properties

68512-30-1 Phenol, methylstyrenated

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information	l.	
 14.1 UN number or ID number ADR, IMDG, IATA 	UN1263	
 14.2 UN proper shipping name ADR 	UN1263 PAINT	
		(Contd. on page

Page 7/9



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 2 (replaces version 1)

Revision: 01.02.2023

Trade name: FEYCOPOX 518 2K HS EG Primer

	(Contd. of page
· IMDG, IATA	PAINT
· 14.3 Transport hazard class(es)	
ADR	
	2 (E1) Elementelle linuide
· Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	111
· 14.5 Environmental hazards:	Not applicable.
 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category 	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
 14.7 Maritime transport in bulk according to IM instruments 	
	Not applicable.
· Transport/Additional information:	
 ADR Limited quantities (LQ) Transport category Tunnel restriction code Remarks: 	5L 3 D/E ≤ 450 l: 2.2.3.1.5 ADR
 IMDG Limited quantities (LQ) Remarks: 	5L ≤ 30 l: 2.2.3.5 IMDG-Code
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

 \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Page 8/9



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 2 (replaces version 1)

Revision: 01.02.2023

(Contd. of page 8)

Trade name: FEYCOPOX 518 2K HS EG Primer

• Qualifying quantity (tonnes) for the application of upper-tier requirem	nents 50,000 t
---	-----------------------

· National regulations:

· Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	10-25

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.
- EUH205 Contains epoxy constituents. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1B: Skin sensitisation - Category 1B STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 * Data compared to the previous version altered. GB