

Page 1/10

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## · 1.1 Product identifier

- · Trade name: FEYCOSIL 241 Silikonharzlack 183 graphitschwarz
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- · Application of the substance / the mixture Paint

## · 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: FEYCOLOR GmbH Maxhüttenstraße 6 93055 Regensburg Germany

Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30 info@feycolor.com www.feycolor.com

Office hours: Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00 Friday: 08:00 - 12:00

Email: sd@feycolor.com www.feycolor.com

· 1.4 Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM)

## **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



Safety data sheet according to 1907/2006/EC, Article 31


Version number 3 (replaces version 2)

Revision: 01.02.2023

Page 2/10

Printing date 01.02.2023

Trade name: FEYCOSIL 241 Silikonharzlack 183 graphitschwarz



• **vPvB:** Not applicable.

## **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

• Dangerous components:		
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-25%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate	<15%
CAS: 78-83-1 EINECS: 201-148-0 Reg.nr.: 01-2119484609-23	Isobutanol ♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Skin Irrit. 2, H315; STOT SE 3, H335-H336	≥1-<2.5%
	(Co	ntd. on page 3)

## 



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

#### Trade name: FEYCOSIL 241 Silikonharzlack 183 graphitschwarz

		(Contd. of page 2)	
CAS: 67-56-1	methanol	<1%	
EINECS: 200-659-6	<ul> <li>♦ Flam. Liq. 2, H225; ♦ Acute Tox. 3, H301; Acute Tox. 3, H311;</li> <li>Acute Tox. 3, H331; ♦ STOT SE 1, H370</li> <li>Specific concentration limits: STOT SE 1; H370: C ≥ 10 %</li> <li>STOT SE 2; H371: 3 % ≤ C &lt; 10 %</li> </ul>		
• Additional information: For the wording of the listed hazard phrases refer to section 16.			

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available. • 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

## **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
  6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
  6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
  6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.
  - See Section 13 for disposal information.

(Contd. on page 4)

GB

Page 3/10



Printing date 01.02.2023

Safety data sheet according to 1907/2006/EC, Article 31

Version number 3 (replaces version 2)

Revision: 01.02.2023

(Contd. of page 3)

Trade name: FEYCOSIL 241 Silikonharzlack 183 graphitschwarz

## **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

· Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

• Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

## · 8.1 Control parameters Ingredients with limit values that require monitoring at the workplace: 1330-20-7 Xylene WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm Long-term value: 220 mg/m<sup>3</sup>, 50 ppm Sk; BMGV 123-86-4 n-Butyl acetate WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm Long-term value: 724 mg/m<sup>3</sup>, 150 ppm 78-83-1 Isobutanol WEL Short-term value: 231 mg/m<sup>3</sup>, 75 ppm Long-term value: 154 mg/m<sup>3</sup>, 50 ppm 67-56-1 methanol WEL Short-term value: 333 mg/m<sup>3</sup>, 250 ppm Long-term value: 266 mg/m<sup>3</sup>, 200 ppm Sk · Ingredients with biological limit values: 1330-20-7 Xylene BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid • Additional information: The lists valid during the making were used as basis. · 8.2 Exposure controls · Appropriate engineering controls No further data; see item 7. · Individual protection measures, such as personal protective equipment · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

GB

Page 4/10



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCOSIL 241 Silikonharzlack 183 graphitschwarz

(Contd. of page 4)

Page 5/10

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes. Avoid contact with the eyes and skin.

#### **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### · Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### · Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties		
<ul> <li>Physical state</li> </ul>	Fluid	
· Colour:	According to product specification	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
<ul> <li>Melting point/freezing point:</li> </ul>	Undetermined.	
Boiling point or initial boiling point and b	ooiling	
range	124-128 °C (123-86-4 n-Butyl acetate)	
· Flammability	Flammable.	
Lower and upper explosion limit		
· Lower:	1.1 Vol % (1330-20-7 Xylene)	
· Upper:	7.5 Vol % (123-86-4 n-Butyl acetate)	
· Flash point:	26 °C (DIN EN ISO 1523:2002)	
Ignition temperature:	370 °C (DIN 51794, 123-86-4 n-Butyl acetate)	
Decomposition temperature:	Not determined.	
	(Contd. on page 6)	



Printing date 01.02.2023

Page 6/10

# Safety data sheet according to 1907/2006/EC, Article 31

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCOSIL 241 Silikonharzlack 183 graphitschwarz

	(Contd. of page 5)
· pH	Not determined.
· Viscosity:	
Kinematic viscosity at 20 °C	>20 s (DIN 53211/4)
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
<ul> <li>Partition coefficient n-octanol/water (log value)</li> </ul>	Not determined.
· Vapour pressure at 20 °C:	10.7 hPa (123-86-4 n-Butyl acetate)
<ul> <li>Density and/or relative density</li> </ul>	
· Density at 20 °C:	1.356 g/cm <sup>3</sup> (DIN EN ISO 2811-1)
· Relative density	Not determined.
· Vapour density	Not determined.
• 9.2 Other information	
· Appearance:	
· Form:	Fluid
<ul> <li>Important information on protection of health an</li> </ul>	ld
environment, and on safety.	
· Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive
	air/vapour mixtures are possible.
· Solvent content:	
· VOC (EC)	37.70 %
<ul> <li>Solids content (weight-%):</li> </ul>	62.3 %
· Change in condition	
· Evaporation rate	Not determined.
Information with regard to physical hazard classe	es
· Explosives	Void
<sup>·</sup> Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
<ul> <li>Self-reactive substances and mixtures</li> </ul>	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable	
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
· Desensitised explosives	Void

## **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

<sup>-</sup> GB



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

(Contd. of page 6)

Trade name: FEYCOSIL 241 Silikonharzlack 183 graphitschwarz

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- $\cdot$  10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

#### **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- STOT-single exposure May cause respiratory irritation.
- STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

## **SECTION 13: Disposal considerations**

#### · 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

GB

Page 7/10



Safety data sheet according to 1907/2006/EC, Article 31

Version number 3 (replaces version 2)

Revision: 01.02.2023

(Contd. of page 7)

Trade name: FEYCOSIL 241 Silikonharzlack 183 graphitschwarz

## · Uncleaned packaging:

· Recommendation:

Printing date 01.02.2023

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN number or ID number		
ADR, IMDG, IATA	UN1263	
14.2 UN proper shipping name		
ADR	UN1263 PAINT	
IMDG, IATA	PAINT	
14.3 Transport hazard class(es)		
ADR		
Class Label	3 (F1) Flammable liquids. 3	
	J	
IMDG, IATA		
3		
Class	3 Flammable liquids.	
Label	3	
14.4 Packing group		
ADR, IMDG, IATA	111	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Warning: Flammable liquids.	
Hazard identification number (Kemler code):	30	
EMS Number:	F-E, <u>S-E</u>	
Stowage Category	A	
14.7 Maritime transport in bulk according to IM		
instruments	Not applicable.	
Transport/Additional information:		
ADR		
Limited quantities (LQ)	5L	
Transport category	3	
Tunnel restriction code	D/E	
IMDG		
Limited quantities (LQ)	5L	



Printing date 01.02.2023

+

Safety data sheet according to 1907/2006/EC. Article 31

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCOSIL 241 Silikonharzlack 183 graphitschwarz

· UN "Model Regulation":

UN 1263 PAINT, 3, III

## **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

• Additional classification according to Decree on Hazardous Materials, Annex II:

Share in %
<1
25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H301 Toxic if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H370 Causes damage to organs.
- H373 May cause damage to organs through prolonged or repeated exposure.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. of page 8)

Page 9/10



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCOSIL 241 Silikonharzlack 183 graphitschwarz

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 1: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 \* \* Data compared to the previous version altered. (Contd. of page 9)

Page 10/10

GB