

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

- · Trade name: FEYCOSIL 244 SI-Kunstharzlack
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: FEYCOLOR GmbH Maxhüttenstraße 6 93055 Regensburg Germany

Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30 info@feycolor.com www.feycolor.com

Office hours: Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00 Friday: 08:00 - 12:00

Email: sd@feycolor.com www.feycolor.com

· 1.4 Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Skin Irrit. 2H315 Causes skin irritation.Eye Irrit. 2H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)





Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOSIL 244 SI-Kunstharzlack

· Hazard pictogra	(Contd. of page 1)
GHS02 GHS07	GHS08
· Signal word War	ning
	ing components of labelling:
Xylene) exemption
Hydrocarbons, CS	
	liquid and vapour.
H315 Causes ski	
H319 Causes ser	ious eye irritation.
	respiratory irritation.
	damage to organs through prolonged or repeated exposure.
· Precautionary st	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P35	3 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	B IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
• Additional inform	
	s cobalt bis(2-ethylhexanoate). May produce an allergic reaction.
• 2.3 Other hazard	s and vPvB assessment
• PBT: Not applical	
• vPvB: Not applica	

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

CAS: 1330-20-7	Xylene	≥10-≤20%
EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	 Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 	
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	<15%
CAS: 7429-90-5 EINECS: 231-072-3 Reg.nr.: 01-2119529243-45	aluminium powder (stabilized)/ manufacturer classification	2.5-<10%



Page 3/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOSIL 244 SI-Kunstharzlack

	(C	ontd. of page 2)
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy, benzene content: < 0,1%	2.5-<10%
EINECS: 265-150-3	🚯 Asp. Tox. 1, H304]
CAS: 100-41-4	Ethylbenzene	<2.5%
EINECS: 202-849-4	🚸 Flam. Liq. 2, H225; 🚸 STOT RE 2, H373; Asp. Tox. 1, H304;	
Reg.nr.: 01-2119489370-35	🚯 Acute Tox. 4, H332; Škin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic	
	Chronic 3, H412	
EC number: 919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	<2.5%
Reg.nr.: 01-2119463258-33	🚸 Flam. Liq. 3, H226; 🚸 Asp. Tox. 1, H304; 🚸 STOT SE 3, H336,	
	EUH066	
CAS: 64742-95-6	Hydrocarbons, C9, aromatics	1-<2.5%
EC number: 918-668-5	🔗 Flam. Liq. 3, H226; 🚸 Asp. Tox. 1, H304; 🚯 Aquatic Chronic 2,	
Reg.nr.: 01-2119455851-35	H411; 🚯 STOT SE 3, H335-H336, EUH066	
	cobalt bis(2-ethylhexanoate)	<0.1%
EINECS: 205-250-6	♦ Repr. 1B. H360Fd: ♦ Aquatic Acute 1. H400: ♦ Eve Irrit. 2. H319:	1
Reg.nr.: 01-2119524678-29	Škin Sens. 1A, H317; Aquatic Chronic 3, H412	
• Additional information: Fo	r the wording of the listed hazard phrases refer to section 16.	L]

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

• 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

⁻ GB



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

(Contd. of page 3)

Page 4/10

Trade name: FEYCOSIL 244 SI-Kunstharzlack

- · 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols. · Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

1330-20-7 Xylene	
WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV	
123-86-4 n-Butyl acetate	
WEL Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm	
7429-90-5 aluminium powder (stabilized)/ manufacturer classificat	ion
WEL Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable dust	
100-41-4 Ethylbenzene	
WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk	
136-52-7 cobalt bis(2-ethylhexanoate)	
WEL Long-term value: 0.1 mg/m ³ as Co; Carc, Sen	
	(Contd. on page



Page 5/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

(Contd. of page 4)

Trade name: FEYCOSIL 244 SI-Kunstharzlack

1330-20-7 Xylene	
BMGA	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid
Additi	onal information: The lists valid during the making were used as basis.
	posure controls
Appro	priate engineering controls No further data; see item 7.
Indivi	dual protection measures, such as personal protective equipment
^	al protective and hydianic measures.

 General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the eyes.
 Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

$^{\circ}$ 9.1 Information on basic physical and chemical properties

· General Information

Physical state

Fluid



Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOSIL 244 SI-Kunstharzlack

	(Contd. of page
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	
range	124-128 °C (123-86-4 n-Butyl acetate)
Flammability	Flammable.
Lower and upper explosion limit	
Lower:	1.1 Vol % (1330-20-7 Xylene)
Upper:	7.5 Vol % (123-86-4 n-Butyl acetate)
Flash point:	24 °C (DIN EN ISO 1523:2002, 1330-20-7 Xylene)
Ignition temperature:	370 °C (DIN 51794)
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	Not determined.
Kinematic viscosity at 20 °C	
Dynamic:	100-120 s (DIN 53211/4) Not determined.
Solubility	Not missible or difficult to miss
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	10.7 hPa (123-86-4 n-Butyl acetate)
Density and/or relative density	
Density at 20 °C:	1.253 g/cm³ (DIN EN ISO 2811-1)
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Appearance.	
Form:	Fluid
Form:	
Form: Important information on protection of health ar	
Form: Important information on protection of health ar environment, and on safety.	nd
Form: Important information on protection of health an environment, and on safety. Auto-ignition temperature:	nd Product is not selfigniting.
Form: Important information on protection of health ar environment, and on safety.	nd Product is not selfigniting. Product is not explosive. However, formation of explosiv
Form: Important information on protection of health an environment, and on safety. Auto-ignition temperature: Explosive properties:	nd Product is not selfigniting.
Form: Important information on protection of health an environment, and on safety. Auto-ignition temperature: Explosive properties: Solvent content:	nd Product is not selfigniting. Product is not explosive. However, formation of explosiv air/vapour mixtures are possible.
Form: Important information on protection of health an environment, and on safety. Auto-ignition temperature: Explosive properties: Solvent content: VOC (EC)	nd Product is not selfigniting. Product is not explosive. However, formation of explosiv air/vapour mixtures are possible. 39.65 %
Form: Important information on protection of health an environment, and on safety. Auto-ignition temperature: Explosive properties: Solvent content: VOC (EC) Solids content (weight-%):	nd Product is not selfigniting. Product is not explosive. However, formation of explosiv air/vapour mixtures are possible.
Form: Important information on protection of health ar environment, and on safety. Auto-ignition temperature: Explosive properties: Solvent content: VOC (EC) Solids content (weight-%): Change in condition	nd Product is not selfigniting. Product is not explosive. However, formation of explosiv air/vapour mixtures are possible. 39.65 % 60.3 %
Form: Important information on protection of health ar environment, and on safety. Auto-ignition temperature: Explosive properties: Solvent content: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate	nd Product is not selfigniting. Product is not explosive. However, formation of explosiv air/vapour mixtures are possible. 39.65 % 60.3 % Not determined.
Form: Important information on protection of health an environment, and on safety. Auto-ignition temperature: Explosive properties: Solvent content: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard class	nd Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapour mixtures are possible. 39.65 % 60.3 % Not determined. es
Form: Important information on protection of health an environment, and on safety. Auto-ignition temperature: Explosive properties: Solvent content: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard classe Explosives	nd Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapour mixtures are possible. 39.65 % 60.3 % Not determined. es Void
Form: Important information on protection of health ar environment, and on safety. Auto-ignition temperature: Explosive properties: Solvent content: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases	nd Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapour mixtures are possible. 39.65 % 60.3 % Not determined. es Void Void Void
Form: Important information on protection of health ar environment, and on safety. Auto-ignition temperature: Explosive properties: Solvent content: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols	nd Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapour mixtures are possible. 39.65 % 60.3 % Not determined. es Void Void Void Void Void
Form: Important information on protection of health ar environment, and on safety. Auto-ignition temperature: Explosive properties: Solvent content: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard class Explosives Flammable gases Aerosols Oxidising gases	nd Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapour mixtures are possible. 39.65 % 60.3 % Not determined. es Void Void Void Void Void Void Void
Form: Important information on protection of health ar environment, and on safety. Auto-ignition temperature: Explosive properties: Solvent content: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases Gases under pressure	nd Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapour mixtures are possible. 39.65 % 60.3 % Not determined. es Void Void Void Void Void
Form: Important information on protection of health ar environment, and on safety. Auto-ignition temperature: Explosive properties: Solvent content: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids	nd Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapour mixtures are possible. 39.65 % 60.3 % Not determined. es Void Void Void Void Void Void Void
Form: Important information on protection of health ar environment, and on safety. Auto-ignition temperature: Explosive properties: Solvent content: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases Gases under pressure	nd Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapour mixtures are possible. 39.65 % 60.3 % Not determined. es Void Void Void Void Void Void Void Void Void Void
Form: Important information on protection of health ar environment, and on safety. Auto-ignition temperature: Explosive properties: Solvent content: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids	nd Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapour mixtures are possible. 39.65 % 60.3 % Not determined. es Void Void Void Void Void Void Void Flammable liquid and vapour.
Form: Important information on protection of health ar environment, and on safety. Auto-ignition temperature: Explosive properties: Solvent content: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids	nd Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapour mixtures are possible. 39.65 % 60.3 % Not determined. es Void
Form: Important information on protection of health ar environment, and on safety. Auto-ignition temperature: Explosive properties: Solvent content: VOC (EC) Solids content (weight-%): Change in condition Evaporation rate Information with regard to physical hazard classe Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures	nd Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapour mixtures are possible. 39.65 % 60.3 % Not determined. es Void



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

(Contd. of page 6)

Trade name: FEYCOSIL 244 SI-Kunstharzlack

	(Conta. of page 6)
Void	
nmable	
Void	
	mable Void Void Void Void Void Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· Skin corrosion/irritation Causes skin irritation.

- · Serious eye damage/irritation Causes serious eye irritation.
- STOT-single exposure May cause respiratory irritation.

• STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

11.2 Information on other hazards

· Endocrine disrupting properties

78-93-3 Methyl ethyl ketone

List II

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

• **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 8)





Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOSIL 244 SI-Kunstharzlack

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

44.4 LIN number or ID number	
14.1 UN number or ID number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG, IATA	UN1263 PAINT PAINT
14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
Label	3
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	F-E, <u>S-E</u>
Stowage Category	A
14.7 Maritime transport in bulk according to IM instruments	Not applicable.
	(Contd. on p

(Contd. of page 7)



Page 9/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOSIL 244 SI-Kunstharzlack

	(Contd. of	page
Transport/Additional information:		
ADR		
Limited quantities (LQ)	5L	
Transport category	3	
Tunnel restriction code	D/E	
Remarks:	≤ 450 I: 2.2.3.1.5 ADR	
IMDG		
Limited quantities (LQ)	5L	
Remarks:	≤ 30 l: 2.2.3.5 IMDG-Code	
UN "Model Regulation":	UN 1263 PAINT, 3, III	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:

Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H360Fd May damage fertility. Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 10)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOSIL 244 SI-Kunstharzlack

(Contd. of page 9)
EUH066 Repeated exposure may cause skin dryness or cracking.
Classification according to Regulation (EC) No 1272/2008
The classification of the mixture is generally based on the calculation method using substance data according to
Regulation (EC) No 1272/2008.
Abbreviations and acronyms:
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International
Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Flam. Sol. 1: Flammable solids – Category 1
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1A: Skin sensitisation – Category 1A
Repr. 1B: Reproductive toxicity – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
* * Data compared to the previous version altered.
GB-