

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Page 1/10

SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: FEYCOZINK Härter 514 schnell 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Hardening agent/ Curing agent 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: **FEYCOLOR GmbH** Maxhüttenstraße 6 93055 Regensburg Germany Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30 info@feycolor.com www.feycolor.com Office hours: Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00 Friday: 08:00 - 12:00 Email: sd@feycolor.com www.feycolor.com 1.4 Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM) **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 flame Flam. Liq. 3 H226 Flammable liquid and vapour. health hazard STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure. corrosion Skin Corr. 1C H314 Causes severe skin burns and eye damage. Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H335 May cause respiratory irritation.

(Contd. on page 2)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

· 2.2 Label elements

Version number 3 (replaces version 2)

Revision: 01.02.2023

(Contd. of page 1)

Trade name: FEYCOZINK Härter 514 schnell

	ccording to Regulation (EC) No 1272/2008 is classified and labelled according to the GB CLP regulation. ograms
GHS02 G	HS05 GHS07 GHS08
· Signal word	Danger
Fatty acids,	ermining components of labelling: C18-unsatd., dimers, polimeric reaction products with tall-oil, fatty acids and triethylenetetramine nethylaminomethyl)phenol
· Hazard stat	
	nable liquid and vapour. es severe skin burns and eye damage.
	ause respiratory irritation.
	ause damage to organs through prolonged or repeated exposure.
	ary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
D303+D361	smoking. +P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or
F 303 F 30 F	shower].
P305+P351	+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P321	Specific treatment (see on this label).
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
· Additional i	
	ntains Amines, polyethylenepoly-, triethylenetetramine fraction. May produce an allergic reaction.
2.3 Other h	
	PBT and vPvB assessment
• PBT: Not ap	
vPvB: Not a	

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3) GB

Page 2/10



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

(Contd. of page 2)

Trade name: FEYCOZINK Härter 514 schnell

	Fatty acids, C18-unsatd., dimers, polimeric reaction products with tall- oil, fatty acids and triethylenetetramine	50-100%
	 Eye Dam. 1, H318 	
Reg.nr.: 01-2119488216-32	Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	25-50%
CAS: 90-72-2 EINECS: 202-013-9 Reg.nr.: 01-2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol Skin Corr. 1C, H314; Eye Dam. 1, H318; � Acute Tox. 4, H302	≥5-<10%
	n-Butyl acetate Flam. Liq. 3, H226;	2.5-<5%
	Amines, polyethylenepoly-, triethylenetetramine fraction Skin Corr. 1B, H314; Eye Dam. 1, H318; O Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<1%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

GB

Page 3/10



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

(Contd. of page 3)

Trade name: FEYCOZINK Härter 514 schnell

 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling
 Ensure good ventilation/exhaustion at the workplace.

 Prevent formation of aerosols.
 Information about fire - and explosion protection:
 Keep ignition sources away - Do not smoke.

 Protect against electrostatic charges.
 Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

• Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.

• Storage class: 3

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

· Ingredients with biological limit values:

1330-20-7 Xylene

BMGV 650 mmol/mol creatinine

- Medium: urine
 - Sampling time: post shift

Parameter: methyl hippuric acid

• Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

• Appropriate engineering controls No further data; see item 7.

(Contd. on page 5)

Page 4/10



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

(Contd. of page 4)

Page 5/10

Trade name: FEYCOZINK Härter 514 schnell

Individual protection measures, such as personal protective equipment
General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties		
• 9.1 Information on basic physical and c	hemical properties	
· General Information		
· Physical state	Fluid	
· Colour:	According to product specification	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
 Melting point/freezing point: 	Undetermined.	
Boiling point or initial boiling point and	boiling	
range	137-143 °C (1330-20-7 Xylene)	
· Flammability	Flammable.	
· Lower and upper explosion limit		
· Lower:	1.1 Vol %	
· Upper:	7 Vol %	
		(Contd. on page 6)



Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCOZINK Härter 514 schnell

	(Contd. of page
Flash point:	24 °C (DIN EN ISO 1523:2002)
Ignition temperature:	500 °C (DIN 51794)
Decomposition temperature:	Not determined.
рН	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic at 20 °C:	>750 mPas
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value	e) Not determined.
Vapour pressure at 20 °C:	, 6.7-8.2 hPa
Density and/or relative density	
Density at 20 °C:	0.938 g/cm³ (DIN EN ISO 2811-1)
Relative density	Not determined.
Vapour density	Not determined.
• •	Hot dotominiou.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health	n and
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosiv
	air/vapour mixtures are possible.
Solvent content:	
VOC (EC)	30.00 %
Solids content (weight-%):	70.0 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard cla	20220
Explosives	Void
Flammable gases	
-	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flamma	
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

(Contd. of page 6)

Trade name: FEYCOZINK Härter 514 schnell

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

 \cdot Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1330-20-7 Xylene		
Oral	LD50	5,251 mg/kg (rat)
Dermal	LD50	5,251 mg/kg (rat) >5,000 mg/kg (rabbit)
Inhalativa	1 C 50/4 h	29 mg/l (rat)

Inhalative LC50/4 h 29 mg/l (rat)

• Skin corrosion/irritation Causes severe skin burns and eye damage.

· Serious eye damage/irritation Causes serious eye damage.

· STOT-single exposure May cause respiratory irritation.

• STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

(Contd. on page 8)



Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

(Contd. of page 7)

Trade name: FEYCOZINK Härter 514 schnell

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14.1 UN number or ID number ADR, IMDG, IATA	UN3469
14.2 UN proper shipping name ADR IMDG, IATA	UN3469 PAINT, FLAMMABLE, CORROSIVE PAINT, FLAMMABLE, CORROSIVE
14.3 Transport hazard class(es)	
ADR	
Class	3 (FC) Flammable liquids.
Label	3+8
IMDG	
Class	3 Flammable liquids.
Label	3/8
ΙΑΤΑ	
Class	3 Flammable liquids.
Label	3 (8)
14.4 Packing group ADR, IMDG, IATA	111
14.5 Environmental hazards:	Not applicable.



Page 9/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCOZINK Härter 514 schnell

	(Contd. of page
· 14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	38
EMS Number:	F-E,S-C
· Stowage Category	A
· Stowage Code	SW2 Clear of living quarters.
· 14.7 Maritime transport in bulk according to IM	10
instruments	Not applicable.
Transport/Additional information:	
ADR	
· Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E
·IMDG	
· Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 3469 PAINT, FLAMMABLE, CORROSIVE, 3 (8), III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

• Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.

(Contd. on page 10)



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 3 (replaces version 2)

Revision: 01.02.2023

Trade name: FEYCOZINK Härter 514 schnell

(Contd. of page 9) May cause respiratory irritation. H335 H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. Classification according to Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Corr. 1C: Skin corrosion/irritation – Category 1C Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 ** Data compared to the previous version altered. GB