

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Page 1/10

SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: FEYCOZINK Härter 515 schnell 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Hardening agent/ Curing agent 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: **FEYCOLOR GmbH** Maxhüttenstraße 6 93055 Regensburg Germany Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30 info@feycolor.com www.feycolor.com Office hours: Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00 Friday: 08:00 - 12:00 Email: sd@feycolor.com www.feycolor.com 1.4 Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM) **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 flame Flam. Liq. 3 H226 Flammable liquid and vapour. health hazard STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure. corrosion Skin Corr. 1C H314 Causes severe skin burns and eye damage. Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H336 May cause drowsiness or dizziness.



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

(Contd. of page 1)

Trade name: FEYCOZINK Härter 515 schnell

| The product i | cording to Regulation (EC) No 1272/2008 is classified and labelled according to the GB CLP regulation. |
|-------------------------------|---|
| Hazard picto | ograms |
| GHS02 GH | 1505 GHS07 GHS08 |
| · Signal word | |
| - | с С |
| | rmining components of labelling: |
| | ethylaminomethyl)phenol |
| Xylene | n ven en el |
| 1-methoxy-2- n-Butyl aceta | |
| · Hazard state | |
| | able liquid and vapour. |
| | s severe skin burns and eye damage. |
| | use drowsiness or dizziness. |
| | use damage to organs through prolonged or repeated exposure. |
| | ry statements |
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P103 | Read carefully and follow all instructions. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P303+P361+ | P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. |
| P305+P351+ | P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if |
| | present and easy to do. Continue rinsing. |
| P310 | Immediately call a POISON CENTER/doctor. |
| P321 | Specific treatment (see on this label). |
| P501 | Dispose of contents/container in accordance with local/regional/national/international |
| . 2 2 Athan ba | regulations. |
| 2.3 Other ha | |
| Results of P | BT and vPvB assessment |

- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3) GB



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOZINK Härter 515 schnell

| Dangerous components: | | |
|--|--|-----------|
| CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35 | 1-methoxy-2-propanol Flam. Liq. 3, H226; STOT SE 3, H336 | 10-25% |
| CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32 | Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | _ ≥10-≤20 |
| CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29 | n-Butyl acetate Flam. Liq. 3, H226; | <15% |
| CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29 | 2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; | 2.5-<10 |
| CAS: 90-72-2 EINECS: 202-013-9 Reg.nr.: 01-2119560597-27 | 2,4,6-tris(dimethylaminomethyl)phenol 🕎 Skin Corr. 1C, H314; Eye Dam. 1, H318; 🚸 Acute Tox. 4, H302 | ≥5-<10 |
| CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35 | Ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412 | 2.5-<10 |
| CAS: 111-76-2 EINECS: 203-905-0 Reg.nr.: 01-2119475108-36 | 2-Butoxyethanol Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg | <2.5% |

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available. • 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

[—] GB



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

(Contd. of page 3)

Trade name: FEYCOZINK Härter 515 schnell

5.3 Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to item 13.

- Ensure adequate ventilation.
- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.

• Storage class: 3

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

| ••••• | | | |
|---------|--|--|--|
| · Ingre | Ingredients with limit values that require monitoring at the workplace: | | |
| 107-9 | 8-2 1-methoxy-2-propanol | | |
| WEL | Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk | | |
| 1330- | 20-7 Xylene | | |
| | Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV | | |
| L | (Contd. on page 5) | | |

Page 4/10

⁻ GB



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOZINK Härter 515 schnell

| 400.0 | | (Contd. of page |
|--------|--|--------------------|
| | 6-4 n-Butyl acetate | |
| | Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm | |
| | 5-6 2-Methoxy-1-methylethyl acetate | |
| | | |
| | Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm | |
| | Sk | |
| 100-4 | 1-4 Ethylbenzene | |
| | Short-term value: 552 mg/m³, 125 ppm | |
| | Long-term value: 441 mg/m ³ , 100 ppm | |
| | Sk | |
| 111-7 | 6-2 2-Butoxyethanol | |
| WEL | Short-term value: 246 mg/m ³ , 50 ppm | |
| | Long-term value: 123 mg/m³, 25 ppm | |
| | Sk, BMGV | |
| Ingree | dients with biological limit values: | |
| | 20-7 Xylene | |
| BMG\ | / 650 mmol/mol creatinine | |
| | Medium: urine | |
| | Sampling time: post shift | |
| | Parameter: methyl hippuric acid | |
| | 6-2 2-Butoxyethanol | |
| BMG\ | / 240 mmol/mol creatinine | |
| | Medium: urine | |
| | Sampling time: post shift | |
| | Parameter: butoxyacetic acid | |
| Addit | ional information: The lists valid during the making were used as basis. | |
| 8.2 E> | xposure controls | |
| | opriate engineering controls No further data; see item 7. | |
| Indivi | dual protection measures, such as personal protective equipment | |
| Gene | ral protective and hygienic measures: | |
| Keep | away from foodstuffs, beverages and feed. | |
| | diately remove all soiled and contaminated clothing | |
| Wash | hands before breaks and at the end of work. | |
| Store | protective clothing separately. | |
| Avoid | contact with the skin. | |
| Avoid | contact with the eyes and skin. | |
| Respi | iratory protection: | |
| | In case of brief exposure or low pollution use respiratory filter device. In case of | intonsivo or long |
| 600 | In case of brief exposure or low pollution use respiratory filter device. In case of | intensive of longe |
| | exposure use self-contained respiratory protective device. | |
| Hand | protection | |
| | tion of the glove material on consideration of the penetration times, rates of diffusion and | the degradation |
| | | |
| | | |



Protective gloves (EN 374)

(Contd. on page 6) - GB



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOZINK Härter 515 schnell

(Contd. of page 5) The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye/face protection



Tightly sealed goggles

| SECTION 9: Physical and chemical properties | |
|---|--|
|---|--|

· 9.1 Information on basic physical and chemical properties · General Information · Physical state Fluid · Colour: According to product specification · Odour: Characteristic · Odour threshold: Not determined. • Melting point/freezing point: Undetermined. · Boiling point or initial boiling point and boiling range 120.3 °C (107-98-2 1-methoxy-2-propanol) Flammability Flammable. · Lower and upper explosion limit · Lower: 1.1 Vol % · Upper: ~20 Vol % 25 °C (DIN EN ISO 1523:2002) · Flash point: · Ignition temperature: 270 °C (DIN 51794) · Decomposition temperature: Not determined. · pH Not determined. · Viscosity: Kinematic viscosity at 20 °C 45 s (DIN 53211/4) · Dynamic: Not determined. · Solubility Not miscible or difficult to mix. · water: · Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure at 20 °C: 12 hPa · Density and/or relative density Density at 20 °C: 0.94 g/cm³ (DIN EN ISO 2811-1) · Relative density Not determined. · Vapour density Not determined. · 9.2 Other information · Appearance: · Form: Fluid (Contd. on page 7) GB



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOZINK Härter 515 schnell

| | (Contd. of page 6) |
|--|---|
| · Important information on protection of healt | th and |
| environment, and on safety. | |
| Auto-ignition temperature: | Product is not selfigniting. |
| Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · Solvent content: | |
| · VOC (EC) | 54.50 % |
| Solids content (weight-%): | 45.5 % |
| Change in condition | |
| · Evaporation rate | Not determined. |
| · Information with regard to physical hazard cl | asses |
| Explosives | Void |
| Flammable gases | Void |
| Aerosols | Void |
| · Oxidising gases | Void |
| Gases under pressure | Void |
| Flammable liquids | Flammable liquid and vapour. |
| Flammable solids | Void |
| Self-reactive substances and mixtures | Void |
| · Pyrophoric liquids | Void |
| Pyrophoric solids | Void |
| Self-heating substances and mixtures | Void |
| Substances and mixtures, which emit flamma | able |
| gases in contact with water | Void |
| [·] Oxidising liquids | Void |
| · Oxidising solids | Void |
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.

· 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- \cdot Skin corrosion/irritation Causes severe skin burns and eye damage.
- Serious eye damage/irritation Causes serious eye damage.
- \cdot STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 8)

Page 7/10



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOZINK Härter 515 schnell

· 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

| UN1263 | |
|-------------------------------|---|
| | |
| UN1263 PAINT RELATED MATERIAL | |
| PAINT RELATED MATERIAL | |
| | (Contd. on page |
| | UN1263 UN1263 PAINT RELATED MATERIAL |

(Contd. of page 7)

Page 8/10



according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

Trade name: FEYCOZINK Härter 515 schnell

| | (Contd. of page 8) |
|---|--|
| 14.3 Transport hazard class(es) | |
| ADR | |
| | |
| · Class | 3 (F1) Flammable liquids. |
| Label | 3 |
| · IMDG, IATA | |
| | |
| · Class | 3 Flammable liquids. |
| · Label | 3 |
| · 14.4 Packing group · ADR, IMDG, IATA | III |
| 14.5 Environmental hazards: | Not applicable. |
| · 14.6 Special precautions for user | Warning: Flammable liquids. |
| Hazard identification number (Kemler code): | 30 |
| EMS Number: Stowage Category | F-E, <u>S-E</u> A |
| • 14.7 Maritime transport in bulk according to IM | |
| instruments | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| Limited quantities (LQ) | 5L |
| Transport category | 3 |
| · Tunnel restriction code | D/E |
| IMDG | |
| · Limited quantities (LQ) | 5L |
| · UN "Model Regulation": | UN 1263 PAINT RELATED MATERIAL, 3, III |

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 10)

Page 9/10



Page 10/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 4 (replaces version 3)

Revision: 01.02.2023

(Contd. of page 9)

Trade name: FEYCOZINK Härter 515 schnell

· National regulations:

· Additional classification according to Decree on Hazardous Materials, Annex II: Class | Share in %

50-100 NK

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- May cause drowsiness or dizziness. H336
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids Category 2 Flam. Liq. 3: Flammable liquids Category 3
- Acute Tox. 4: Acute toxicity Category 4
- Skin Corr. 1C: Skin corrosion/irritation Category 1C Skin Irrit. 2: Skin corrosion/irritation - Category 2
- Eye Dam. 1: Serious eye damage/eye irritation Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) Category 2
- Asp. Tox. 1: Aspiration hazard Category 1
- Aquatic Chronic 3: Hazardous to the aquatic environment long-term aquatic hazard Category 3
- * * Data compared to the previous version altered.