



according to 1907/2006/EC, Article 31

Printing date 02.06.2022 Version number 51 Revision: 02.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: RELAFLOOR 1570 2K EP HS Härter
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Epoxy curing agent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

FEYCOLOR GmbH Maxhüttenstraße 6 93055 Regensburg Germany

Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30

info@feycolor.com www.feycolor.com

Office hours:

Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00

Friday: 08:00 - 12:00

Email: sd@feycolor.com www.feycolor.com

1.4 Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)





according to 1907/2006/EC, Article 31

Printing date 02.06.2022 Version number 51 Revision: 02.06.2022

Trade name: RELAFLOOR 1570 2K EP HS Härter

(Contd. of page 1)

· Hazard pictograms





GHS05 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

Benzyl alcohol

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer m-phenylenebis(methylamine)

Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label). P321

P362+P364 Take off contaminated clothing and wash it before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

· 2.3 Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	25-50%
EINECS: 220-666-8	3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	≥10-<25%
	Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer Skin Corr. 1B, H314; Eye Dam. 1, H318	10-25%

(Contd. on page 3)





according to 1907/2006/EC, Article 31

Printing date 02.06.2022 Version number 51 Revision: 02.06.2022

Trade name: RELAFLOOR 1570 2K EP HS Härter

	(C	ontd. of page 2)
CAS: 1477-55-0	m-phenylenebis(methylamine)	≥10-<25%
EINECS: 216-032-5	Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412	
Reg.nr.: 01-2119480150-50	4, H332; Skin Sens. 1, H31/; Aquatic Chronic 3, H412	
CAS: 61788-44-1	Phenol, styrenated	2.5-<10%
EINECS: 262-975-0	Aquatic Chronic 2, H411; (1) Skin Irrit. 2, H315; Skin Sens. 1, H317	
Reg.nr.: 01-2119980970-27		

[•] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Call for a doctor immediately.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Page 4/9

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.06.2022 Version number 51 Revision: 02.06.2022

Trade name: RELAFLOOR 1570 2K EP HS Härter

(Contd. of page 3)

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about fire and explosion protection: Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 8 A
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)





according to 1907/2006/EC, Article 31

Printing date 02.06.2022 Version number 51 Revision: 02.06.2022

Trade name: RELAFLOOR 1570 2K EP HS Härter

(Contd. of page 4)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· 9.1 Information on	basic physical	and chemical	properties

· General Information

· Appearance:

Form: Fluid

Colour: According to product specification

• Odour: Characteristic
• Odour threshold: Not determined.

· pH-value at 20 °C:

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: 205.4 °C

• Flash point: 130 °C (DIN 53213)

• Flammability (solid, gas): Not applicable.

· **Ignition temperature:** >300 °C (DIN 51794)

• **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower: 1.3 Vol % **Upper:** 13 Vol %

· Vapour pressure at 20 °C: <1 hPa

Density at 20 °C: 1.047 g/cm³ (DIN 53217)

Relative density
Vapour density
Evaporation rate
Not determined.
Not determined.
Not determined.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

(Contd. on page 6)





according to 1907/2006/EC, Article 31

Printing date 02.06.2022 Version number 51 Revision: 02.06.2022

Trade name: RELAFLOOR 1570 2K EP HS Härter

		(Contd. of page 5)
Viscosity:		
Dynamic at 20 °C:	200 mPas	
Kinematic:	Not determined.	
Solvent content:		
VOC (EC)	0.00 %	
Solids content (weight-%):	100.0 %	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if swallowed.

· LD/LC50 values relevant for classification:

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral LD50 1,030 mg/kg (rat)

- Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.

(Contd. on page 7)





according to 1907/2006/EC, Article 31

Printing date 02.06.2022 Version number 51 Revision: 02.06.2022

Trade name: RELAFLOOR 1570 2K EP HS Härter

(Contd. of page 6)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- **Ecotoxical effects:**
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

ı	SECTION	14:	Transport information
---	---------	-----	-----------------------

· 14.1 UN-Number · ADR, IMDG, IATA	UN2735
· 14.2 UN proper shipping name	UNIQUE AMINES LIGHT CORROSIVE NO.S
· ADR	UN2735 AMINES, LIQUID, CORROSIVE, N.O.S.
	(ISOPHORONEDIAMINE, m-phenylenebis(methylamine))
· IMDG, IATA	AMINES, LIQUID, CORROSIVE, N.O.S.
	(ISOPHORONEDIAMINE, m-phenylenebis(methylamine))

- · 14.3 Transport hazard class(es)
- \cdot ADR



· Class 8 (C7) Corrosive substances.

·Label

(Contd. on page 8)





according to 1907/2006/EC, Article 31

Printing date 02.06.2022 Version number 51 Revision: 02.06.2022

Trade name: RELAFLOOR 1570 2K EP HS Härter

(Contd. of page 7)

· IMDG, IATA 8 Corrosive substances. · Class ·Label · 14.4 Packing group · ADR, IMDG, IATA Ш · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Corrosive substances. · Hazard identification number (Kemler code): · EMS Number: F-A,S-B · Segregation groups Alkalis · Stowage Category · Segregation Code SG35 Stow "separated from" SGG1-acids · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information:

5L 3

Е

5L

UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S.

(ISOPHORONEDIAMINE,

PHENYLENEBIS(METHYLAMINE)), 8, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU

· Limited quantities (LQ)

· Tunnel restriction code

· Limited quantities (LQ)

· UN "Model Regulation":

Transport category

· ADR

· IMDG

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

(Contd. on page 9)





according to 1907/2006/EC, Article 31

Printing date 02.06.2022 Version number 51 Revision: 02.06.2022

Trade name: RELAFLOOR 1570 2K EP HS Härter

(Contd. of page 8)

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

 \cdot * Data compared to the previous version altered.

GB