

according to 1907/2006/EC, Article 31

Printing date 09.07.2021

Version number 4

Revision: 19.05.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

[•] 1.1 Product identifier

· Trade name: RELAFLOOR 3600 2K PU Beschichtung WV

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- · Application of the substance / the mixture Paint

· 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: FEYCOLOR GmbH Maxhüttenstraße 6 93055 Regensburg Germany

Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30 info@feycolor.com www.feycolor.com

Office hours: Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00 Friday: 08:00 - 12:00

Email: sd@feycolor.com www.feycolor.com

• 1.4 Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

- · Classification according to Regulation (EC) No 1272/2008 The product is not classified, according to the CLP regulation.
- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:
- EUH208 Contains C(M)IT/MIT (3:1). May produce an allergic reaction.
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition	on/information on ingredients	
• 3.2 Chemical characterisat • Description: Mixture of sub	ion: Mixtures stances listed below with nonhazardous additions.	
· Dangerous components:		
	2-butoxyethanol	2.5-<10%
EINECS: 203-905-0	() Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2,	
Reg.nr.: 01-2119475108-36	H315; Eye Irrit. 2, H319	
	(Cor	ntd. on page 2)



according to 1907/2006/EC, Article 31

Revision: 19.05.2020

Printing date 09.07.2021

Version number 4

Trade name: RELAFLOOR 3600 2K PU Beschichtung WV

	(Co	ontd. of page 1)
CAS: 123-42-2	4-hydroxy-4-methylpentan-2-one	<2.5%
EINECS: 204-626-7	🛞 Flam. Liq. 3, H226; 🚯 Eye Irrit. 2, H319; STOT SE 3, H335	
Reg.nr.: 01-2119473975-21		
CAS: 64771-71-7	Paraffins (petroleum), normal C>10	<2.5%
EINECS: 265-232-9	🐼 Asp. Tox. 1, H304	
• Additional information: Fo	or the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:
- Dilute with plenty of water.
- Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

No special measures required.

No special precautions are necessary if used correctly.

- \cdot Information about fire and explosion protection: No special measures required.
- ·7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.

(Contd. on page 3)

Page 2/7



according to 1907/2006/EC, Article 31

Printing date 09.07.2021

Version number 4

Revision: 19.05.2020

(Contd. of page 2)

Trade name: RELAFLOOR 3600 2K PU Beschichtung WV

· Further information about storage conditions: Protect from frost.

• Storage class: 12

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see item 7.

[•] Ingredients with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol

WEL Short-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm Sk, BMGV

123-42-2 4-hydroxy-4-methylpentan-2-one

WEL Short-term value: 362 mg/m³, 75 ppm

Long-term value: 241 mg/m³, 50 ppm

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BMGV 240 mmol/mol creatinine Medium: urine Sampling time: post shift

Parameter: butoxyacetic acid

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- Respiratory protection: Use suitable respiratory protective device only when aerosol or mist is formed.

· Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Goggles recommended during refilling

SECTION 9: Physical and chemical properties		
• 9.1 Information on basic • General Information • Appearance:	physical and chemical properties	
Form:	Fluid	
Colour:	According to product specification	
· Odour:	Characteristic	
		(Contd. on page 4)
		GE



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.07.2021

Version number 4

Revision: 19.05.2020

Trade name: RELAFLOOR 3600 2K PU Beschichtung WV

		(Contd. of page 3)
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
 Change in condition Melting point/freezing point: Initial boiling point and boiling range 	Undetermined. : 100 °C	
· Flash point:	Not applicable.	
· Flammability (solid, gas):	Not applicable.	
· Ignition temperature:	240 °C (DIN 51794)	
· Decomposition temperature:	Not determined.	
· Auto-ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product does not present an explosion hazard.	
· Explosion limits: Lower: Upper:	Not determined. Not determined.	
· Vapour pressure at 20 °C:	23 hPa	
 Density at 20 °C: Relative density Vapour density Evaporation rate 	1.23 g/cm³ (DIN EN ISO 2811-1)Not determined.Not determined.Not determined.	
· Solubility in / Miscibility with water:	Fully miscible.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.	
· Solvent content: Water: VOC (EC)	45.8 % 9.96 %	
Solids content (weight-%):	44.2 %	
• 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 5)

GB

Page 4/7



according to 1907/2006/EC, Article 31

Printing date 09.07.2021

Version number 4

Revision: 19.05.2020

(Contd. of page 4)

Trade name: RELAFLOOR 3600 2K PU Beschichtung WV

· 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 12 waste paint and varnish other than those mentioned in 08 01 11

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

(Contd. on page 6)

GB

Page 5/7



according to 1907/2006/EC, Article 31

Printing date 09.07.2021

Version number 4

Revision: 19.05.2020

(Contd. of page 5)

Trade name: RELAFLOOR 3600 2K PU Beschichtung WV

SECTION 14: Transport information		
· 14.1 UN-Number · ADR, ADN, IMDG, IATA	Void	
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
· 14.7 Transport in bulk according to Annex I and the IBC Code	I of Marpol Not applicable.	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· National regulations:

· Additional classification according to Decree on Hazardous Materials, Annex II:

Class Share in %

NK ≥3-<10

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.

GB

Page 6/7



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.07.2021

Version number 4

Revision: 19.05.2020

Trade name: RELAFLOOR 3600 2K PU Beschichtung WV

	(Contd. of page 6)
Classification according to Regulation (EC) No 1272/2008	
The classification of the mixture is generally based on the calculation method using substance data according to the substance	rding to Regulation
(EC) No 1272/2008.	
Abbreviations and acronyms:	
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the Internationa	l Carriage of Dangerous
Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOC: Volatile Organic Compounds (USA, EU)	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Asp. Tox. 1: Aspiration hazard – Category 1	

Page 7/7