

according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 12.07.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: RELAMIX PLUS 207 Paste violett 410 · UFI: 4081-Y049-D00F-4E96 · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Stainer · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: FEYCOLOR GmbH Maxhüttenstraße 6 93055 Regensburg Germany Tel.: +49 (0) 941-60497-0 Fax: +49 (0) 941-60497-30 info@feycolor.com www.feycolor.com Office hours: Monday - Thursday: 08:00 - 12:00 und 13:00 - 16:00 Friday: 08:00 - 12:00 Email: sd@feycolor.com www.feycolor.com • 1.4 Emergency telephone number: +49 (0) 700 24 11 21 12 (FCM) **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

 • 2.2 Label elements
 • Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
 • Hazard pictograms



· Signal word Warning

(Contd. on page 2)

GB



according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 12.07.2021

(Contd. of page 1)

Trade name: RELAMIX PLUS 207 Paste violett 410

	mining components of labelling:
2-Methoxy-1-n	nethylethyl acetate
n-Butyl acetate	
· Hazard staten	nents
H226 Flammab	ble liquid and vapour.
	se drowsiness or dizziness.
· Precautionary	<i>v</i> statements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P3	353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
2.3 Other haza	ards
· Results of PB	Γ and vPvB assessment
PBT: Not appl	icable

PBT: Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; () STOT SE 3, H336	25-50%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate Flam. Liq. 3, H226; (1) STOT SE 3, H336	5-<10%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	① Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	2.5-<5%
	r the wording of the listed hazard phrases refer to section 16	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.

• After swallowing: If symptoms persist consult doctor.

- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

(Contd. on page 3)

GB

Page 2/8



according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 12.07.2021

(Contd. of page 2)

Trade name: RELAMIX PLUS 207 Paste violett 410

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

• Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- \cdot 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- 6.4 Reference to other sections
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about fire and explosion protection:
- Keep ignition sources away Do not smoke.
- Protect against electrostatic charges.
- ·7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.

• Storage class: 3

•7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

Sk

(Contd. on page 4)

GR

Page 3/8



according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 12.07.2021

Trade name: RELAMIX PLUS 207 Paste violett 410

_		(Contd. of page 3)
	123-86-4 n-Butyl acetate	
Ī	WEL Short-term value: 966 mg/m ³ , 200 ppm	
	Long-term value: 724 mg/m ³ , 150 ppm	
	112-07-2 2-Butoxyethyl acetate	
	WEL Short-term value: 332 mg/m ³ , 50 ppm	
	Long-term value: 133 mg/m ³ , 20 ppm	

Sk

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

• General protective and hygienic measures: Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties • 9.1 Information on basic physical and chemical properties • General Information • Appearance: Form: Fluid Colour: According to product specification • Odour: Characteristic



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 12.07.2021

Trade name: RELAMIX PLUS 207 Paste violett 410

	(Contd. of page 4
· Odour threshold:	Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/freezing point: Initial boiling point and boiling range 	Undetermined. e: 124-128 °C
· Flash point:	32 °C (DIN 53213)
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	370 °C (DIN 51794)
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixture are possible.
[·] Explosion limits: Lower: Upper:	1.5 Vol % 10.8 Vol %
· Vapour pressure at 20 °C:	10.7 hPa
 Density at 20 °C: Relative density Vapour density Evaporation rate 	1.146 g/cm ³ (DIN 53217) Not determined. Not determined. Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic at 20 °C: Kinematic:	10,000 mPas Not determined.
· Solvent content: VOC (EC)	45.74 %
Solids content (weight-%):	54.2 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)

GB

Page 5/8



according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 12.07.2021

(Contd. of page 5)

Trade name: RELAMIX PLUS 207 Paste violett 410

· 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- \cdot Recommendation: Disposal must be made according to official regulations.

(Contd. on page 7)

GB

Page 6/8



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 12.07.2021

(Contd. of page 6)

Trade name: RELAMIX PLUS 207 Paste violett 410

14.1 UN-Number	
ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name	
ADR	UN1263 PAINT
IMDG, IATA	PAINT
14.3 Transport hazard class(es)	
ADR	
Class	2 (E1) Elemmoble liquids
Label	3 (F1) Flammable liquids.
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	F-E,S-E
Stowage Category	A
14.7 Transport in bulk according to Annex II of Ma	
and the IBC Code	Not applicable.
Transport/Additional information:	
ADR Limited grantities (LO)	51
Limited quantities (LQ)	5L
Transport category	3 D/F
Tunnel restriction code	D/E
Remarks:	≤ 450 l: -
IMDG	
Limited quantities (LQ)	5L
Remarks:	≤ 30 l: -
Kemarky.	—

(Contd. on page 8)

Page 7/8



according to 1907/2006/EC, Article 31

Printing date 12.07.2021

Version number 2

Revision: 12.07.2021

(Contd. of page 7)

Trade name: RELAMIX PLUS 207 Paste violett 410

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

• DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· National regulations:

· Additional classification according to Decree on Hazardous Materials, Annex II:

Class Share in %

NK 25-50

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

• Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

• * Data compared to the previous version altered.

Page 8/8